



975GN Equipment Trailer



Extruded Aluminum Deck

Lighten your load

Allow us to introduce you to a better line of products...

A Quality Aluminum Product that Hauls More Payload

Model 975GN Equipment Trailer Standard Specifications

Main frame 6061-T6 Extruded aluminum arched I beam
 Side rail 5" with radius corners
 Floor is 1/2" extruded interlocking planks
 Cross members extruded 4" I beam 16" on center
 Ramp bars 1 1/2" X 2 1/2" D tube with none slip surface
 Axles slipper spring with Oil lube hubs
 Brakes electric all axles

Tires radial trailer tires
 Wheels painted steel silver
 Coupler type adjustable height
 Jack 2 speed dual drop leg 10,000 lb cap
 All electrical connections heat sealed
 Stop tail turn and I.D. clearance lights LED

CODE	Width	Length	Axles	Tires	Coupler	WT
30000 LB. GVWR 14" I Beam						
975XL533K-30K-96-24	102"	24'	2	215/75R17.5H	N/A	3986
975XL533K-30K-96-26	102"	26'	2	215/75R17.5H	N/A	4101
975XL533K-30K-96-28	102"	28'	2	215/75R17.5H	N/A	4216
975XL533K-30K-96-30	102"	30'	2	215/75R17.5H	N/A	4331
975XL533K-30K-96-32	102"	32'	2	215/75R17.5H	N/A	4446
975XL533K-30K-96-34	102"	34'	2	215/75R17.5H	N/A	4561
975XL533K-30K-96-36	102"	36'	2	215/75R17.5H	N/A	4676
975XL533K-30K-96-38	102"	38'	2	215/75R17.5H	N/A	4791
GNO30K	Gooseneck					128
RE2048FU	20" X 48" Ramps fold up (pair)					120
RE2060FU	20" X 60" Ramps fold up (pair)					150
RE2048FO	20" X 48" Ramps fold over (pair)					130

Ramp Options



Fold up ramps



Fold over ramps

Standard Features



2 Speed dual drop leg jacks



Anti torque structure



Chain & binder storage box



Upper GN Box & loading lights

Customizing Options



Chain tie slots



Under body tool box



Dunege box



Gooseneck platform



Aluminum wheels



Steps



Stake pockets & rub rail



Under deck tie bar



Go green

increase your Fuel economy with an Aluminum Trailer



801 Industrial Dr. Wildwood, FL 34785
 Phone: 352 748-3229 Fax: 352-748-6982

www.alumne.com